## NH 55-56 in 55 HP (2 WD)



Engine Power	55HP
Operating Weight	2070 Kg.
No.of Cylinders	3
Bore Stroke	100 X 115 mm
Piston Displacement	2710 cc
Maximum Power	@ 2500rpm
Maximum Torque	@ 1500rpm
Pump	Distribution Injection type.
Battery	12 Volts 105 Ah.
Air Filter	Oil bath
Fuel Filter	02 replaceable cartridges
Fuel Tank Capacity	61 Liters
Transmission	Gear box with constant mesh gears:8 forward and 2 reverse speeds: Synchromesh on
	3rd,4th,7th,& 8th speeds.
Brakes	Service Disc type, oil bath, mechanical control, simultaneous or independent
Brakes (Parking)	Dependent, operating on service brakes, with hand control lever and flashing light.
Steering	Hydrostatic power steering with independent circuit
	Deluxe, with parallelogram suspension and hydraulic shock absorber, adjustable to
Driver's seat	driver's weight, reach and height.
Power Take Off	540rpm (1 3/8"-6 spline Shaft)@ 1970 engine rpm
Hyd. Pump	Gear type pump driven from engine.
Pump Capacity	34.5 L/min.
Maximum lifting capacity	2200 Kg.
Tyre (Front)	6.00-16
Tyre (Rear)	14.9/13-28
D.T.O.	Speed same as engine -Anti clockwise optional.

515-C, Nizam Block, Allama Iqbal Town, Lahore, Pakistan
URL: www.elixirexport.com
Contact: +923314122833
E-Mail: info@elixirexport.com